

Cartons for this Play Set:

| | |
|--------------|--------------------------------------|
| 1 63007-421 | Lexington Box 1 (Hardware) |
| 1 63007-422 | Lexington Box 2 |
| 1 63007-423 | Lexington Box 3 |
| 1 63007-445 | Lexington Wood Roof (Hdwre & Instr) |
| 1 SH946-102 | Access Ladder, 5ft |
| 1 AG942-400 | Access Handles (Hdwre & Instr) |
| 1 63058-202 | 4 Position Swing Beam |
| 1 63060-222 | 9ft Swing Beam Legs (Hdwre & Instr) |
| 1 32404-102 | Wall Slat - 5/4 x 6 x 31-1/2" |
| 1 50546-777 | 3 Swings, 1 Trapeze |
| 1 8364-400 | 10 ft Scoop Slide |
| 1 AH201-102Q | Rock Climber (Hdwre & Instr) |
| 1 SC909-800Q | Lexington Play Walls (Hdwre & Instr) |
| 1 SC910-800Q | Lexington Play Floor (Hdwre & Instr) |

Dimensions of assembled package:
17' 0" wide x 14' 6" deep x 11' 6" tall



The components of this gym can be combined with others to create different play sets. This is the best order of assembly to create this specific set.

Read this sheet and all instructions included with the different parts before assembly.

See the Instructions and Owner's Manual included in carton 63007-445 for important safety information.

- Start by assembling the Lexington tower. Instructions and hardware are in the cartons noted above.
- Wait to install the Access Ladder, Slide, and Wall Slats until after the rest of the play set is complete.
- Lexington step 21. No Swing Mount is needed.
- Install the 9ft Swing Beam. Instructions are in carton 63060-222.
- Install the Play Floor (SC910-800Q).
- Install the Play Walls (SC909-800Q) on front and swing side of the tower.
- Install the Rock Climbing Wall (AH201-102Q) in the position shown.
- Place the access ladder and slide as shown above. Check spacing.
- Fasten access brackets to the **inside** of the ladder rails. Secure the access ladder using the method shown in step 20 of the Lexington instructions.
- Fasten the Access Ladder Handles (AG942-400) to the Access Ladder.
- Install the slide mount and slide using the method shown in steps 28 and 29 of the Lexington instructions.
- Install wall slats in the positions shown above, using the methods from the Lexington instructions. Gaps must be narrower than 3-1/2" or wider than 9" to prevent potential head entrapment.
- Mount one hand grip to the entrance wall slat between the ladder and the slide. Mount the other hand grip to the adjacent post at the same height, using 1/4 x 1-1/2" lag screws and 1/4" flat washers. Drill 3/16" diameter pilot holes for the lag screws.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.