



Dimensions of assembled package:
19' 4" wide x 14' 6" deep x 11' 6" tall

The components of this gym can be combined with others to create different play sets.
This is the best order of assembly to create this specific set.

Read this sheet and all instructions included with the different parts before assembly.

See the Instructions and Owner's Manual included in carton 63006-445 for important safety information.

Cartons for this Play Set:

1	63006-421	Williamsburg Box 1 (Hardware)
1	63006-422	Williamsburg Box 2
1	63006-423	Williamsburg Box 3
1	63006-445	Williamsburg Roof (Hdwre & Instr)
1	SH946-102	Access Ladder, 5ft
1	63058-202	4 Position Swing Beam
1	63060-222	9ft Swing Beam Legs (Hdwre & Instr)
1	50546-777	3 Swings, 1 Trapeze
1	15166-400	10 ft. Super Wave Slide
1	AH201-102Q	Rock Climber (Hdwre & Instr)
1	SC907-800Q	Williamsburg Play Walls (Hdwre & Instr)
1	SC908-800Q	Williamsburg Play Floor (Hdwre & Instr)
1	63081-102	Ice Cream Stand (Hdwre & Instr)
1	AG942-400	Access Ladder Handles (Hdwre & Instr)
1	AG943-400	Slide Handle (Hdwre & Instr)
1	SM964-402	Gable Fans (Hdwre & Instr)
1	SM963-402	Dormer (Hdwre & Instr)

- Start by assembling the Williamsburg tower. Instructions and hardware are in the cartons noted at left.
- Wait to install the Access Ladder, Slide, and Wall Slats until after the rest of the play set is complete.
- Wmsbg steps 7 & 8. Do not install the angle brace mounted to the back platform end nearest the swings. It will interfere with the chalkboard.
- Skip Wmsbg steps 20 & 21.

After completing the tower except Access Ladder, Slide, and Wall Slats:

- Using a ladder, install the Dormer (SM963-402) in the position shown. Ladder access may be obstructed by later installations.
- Install the Gable Fans (SM964-402).
- Install the 9ft Swing Beam. Instructions are in carton 63060-222.



- Install the Play Floor (SC908-800Q).
- Install the Play Walls (SC907-800Q) on front and swing side of the tower.
- Install the Ice Cream Stand (63081-102) on the back of the tower.
- Install the Rock Climbing Wall (AH-201Q) in the position shown.
- Place the access ladder and slide as shown in the picture on the preceding page. Check spacing.
- Fasten access brackets to the **inside** of the ladder rails. Secure the access ladder using the method shown in step 18 of the Williamsburg instructions.
- Fasten the Access Ladder Handles (AG942-400) to the Access Ladder.
- Install the slide mount and slide using the method shown in steps 27 and 28 of the Williamsburg instructions.
- Install wall slats in the positions shown on the front page, using the methods from the Williamsburg Instructions. Gaps must be narrower than 3-1/2" or wider than 9" to prevent potential head entrapment.
- Mount one hand grip to the entrance wall slat between the ladder and the slide. Mount the other hand grip to the adjacent post at the same height, using 1/4 x 1-1/2" lag screws and 1/4" flat washers. Drill 3/16" diameter pilot holes for the lag screws.
- Mount the Slide Handle (AG943-400) above the Super Wave Slide.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.